



NIGHT VISION BINOCULARS

NIGHT SCOUT

If you want the best technologically advanced 1st Gen. pair of Night Vision binoculars available, look no further. We present you with the ATN Night Scout, "Smart" binoculars. These binoculars come with a pair of high resolution 1st Gen. image intensifier tubes, which provide you with a very sharp and bright image. The computerized proximity sensor, once activated, turns the unit on when in viewing position and off when not. The heavy-coated 90mm glass lenses allow for optimum clarity and distance. The best part is that if there is no light to amplify, with the help of the infra-red illuminator, you can cut through the darkness.

- Outfitted with ATN exclusive Smart features
- Powerful 5x magnification
- Automatic on/off proximity sensor
- High resolution Gen 1+ image intensifier tubes
- Multi-coated all-glass optics
- Long Range infrared illuminator
- Water and fog resistant
- Limited Two-Year Warranty



SPECIFICATIONS

MAGNIFICATION	5x
LENS SYSTEM	6 (9) elements; F1. 2, 90mm
FIELD OF VIEW	20°
RANGE OF FOCUS	20m to
POWER SUPPLY	two 3 volt lithium
BATTERY LIFE	10-20 hours
OPERATING TEMPERATURE	-40°C to +50°C
STORAGE TEMPERATURE	-50°C to +70°C
DIMENSIONS	225mm x 150mm x 60mm
WEIGHT	1.5kg.

ACCESSORIES



CAMERA ADAPTER
ACMUCA01



IR-450
ACMUIR45B1

TUBE SPECIFICATIONS

HIGH QUALITY 1+ GEN IMAGE INTENSIFIER TUBE

DESCRIPTION	Standard
GENERATION	1+
RESOLUTION. lp/mm*	40
EXPORT	Available

* Specifications are provided for informational purposes only. Actual values may vary

Export Warning: These products are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.

1341 San Mateo Ave,
South San Francisco, CA 94080.

www.atncorp.com
e-mail: sales@atncorp.com, info@atncorp.com

Tel: 800-910-2862, 650-989-5100,
fax: 650-875-0129